



AdvanceGuard™

HDX 50 Natural Gas Engine Antifreeze Coolant

Product Description

AdvanceGuard™ HDX 50 Natural Gas Engine Antifreeze Coolant is ready-fill ethylene glycol-based (EG) coolant-antifreeze specifically designed for large stationary natural gas engines and interstage coolers. It is formulated for extended life and corrosion protection in heavy-duty systems. It contains a **long-life inhibitor additive** using advanced hybrid (Nitrite/Molybdate) plus Organic Acid Technology (OAT) coolant inhibitor technology. The AdvanceGuard™ HDX 50 Natural Gas Engine Antifreeze Coolant inhibitors protect against damaging rust and corrosion in stationary industrial engines and cooling systems. Mineral scale deposits are controlled by a high-performance scale inhibition polymer, which improves overall performance in operating systems that encounter poor water quality in the field.

Typical Physical Properties

Form@70°F	Blue-Green Liquid
Glycol Concentration, %	50 (Monoethylene Glycol)
Relative Density 60°F (15.5°C)	1.10 to 1.12
Density, (lbs/gal)	8.1 to 8.5 (typical)
Freeze Point, °F (°C)	-34 (-37) max
Boiling Point, °F (°C)	265 (129) min (29.7 psia)
pH, (10% Solution)	8.5 - 9.5
Dilution Water	Deionized Low TDS (<500 ppm)

Application Information

AdvanceGuard™ HDX 50 Natural Gas Engine Antifreeze Coolant is ready-fill (no dilution needed) for the coolant system. Existing coolant systems should be cleaned and flushed with **AdvanceClean™ EJC 100 or EJC 200** Engine Jacket Cleaner, followed by a flush with low TDS water before adding **AdvanceGuard™ HDX 50 Natural Gas Engine Antifreeze Coolant** to the compressor cooling system.

Performance & Compatibility

AdvanceGuard™ HDX 50 Natural Gas Engine Antifreeze Coolants are formulated to meet or be compatible with the performance requirements of the following industry and OEM standards (based on additive performance).

ASTM D3306, D4985, D6210	SAE J1034, J1038
CAT ELC (EC-1) & Cummins 90T8-4	Detroit Diesel 7SE298
GM 1825M, 1899M, 6277M	Freightliner 48-22880, TMC RP329

Handling & Precautions

AdvanceGuard™ HDX 50 Natural Gas Engine Antifreeze Coolant is available in 5-gal buckets, 55-gallon drums, 275-gal one-way tote tanks, and bulk truck volumes. **AdvanceGuard™ HDX 50 Natural Gas Engine Antifreeze Coolant** is an industrial chemical. It should only be handled by those persons who have read and are familiar with the handling precautions provided in the product's safety data sheet.

301A Milton Avenue, Lafayette, Louisiana 70508 • www.chemadvances.com • 1-800-847-5121

Recommendations given in this bulletin are based on tests believed to be reliable. However, the use of the information is beyond the control of Chem Advances, LLC and no guarantee, expressed or implied is made to the results obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage from the misuse of the product as such, or in combination with other materials. This bulletin is not to be taken as a license to operate under or recommendation to infringe any patent.

Conventional Characteristics

Appearance	Blue/Green
Specific Gravity, (60/60F) ASTMD1122	1.110
pH (33% solution) ASTMD1287	8.3
Reserve Alkalinity ASTMD1121	5.5
Ash content, % max.	5.0
Freeze Protection (Pressure Independent, ASTMD1177) 60% EG 50% EG 40% EG 30% EG	-67 °F (-54 °C) -34 °F (-37 °C) -8 to -12 °F (-23 °C) 5 °F (-15 °C)
Boiling Protection 15 lb pressure cap (29.7 psia) 60% EG 50% EG 40% EG 30% EG Water	~ 270 - 275 °F (132 - 135 °C) ~ 265 °F (129 °C) ~ 262-267 °F (128-131 °C) ~ 270-275 °F (132-135 °C) ~250 °F (121 °C)
Nitrites	> 400 ppm
Molybdate	> 400 ppm
Silicate, %	- 0 -
Phosphate, %	- 0 -
Amine, %	- 0 -
Borate, %	- 0 -
Nitrates, %	- 0 -
<i>* These values are typical values and should not be used as a quality control parameter either to accept or reject product. Specifications are subject to change without notice.</i>	
Additive Technology	Carboxylic Acid Tolytriazole Nitrites Molybdate
SCA Required	No (optional)
Aluminum compatible	Yes

301A Milton Avenue, Lafayette, Louisiana 70508 • www.chemadvances.com • 1-800-847-5121

Recommendations given in this bulletin are based on tests believed to be reliable. However, the use of the information is beyond the control of Chem Advances, LLC and no guarantee, expressed or implied is made to the results obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage from the misuse of the product as such, or in combination with other materials. This bulletin is not to be taken as a license to operate under or recommendation to infringe any patent.